

IN THE CLAIMS:

Please cancel Claim 9 and incorporate the substance thereof into Claim 1,  
add new Claims 26 to 37, and amend the remaining claims as follows:

1. (Currently amended) A rechargeable lithium battery which comprises a  
single battery main body <sup>which comprises</sup> ~~comprising at least~~ a cathode, an anode, and an ion conductor  
enclosed between <sup>said</sup> pair of <sup>said</sup> sealing member (a) and <sup>said</sup> sealing member (b), at least said  
sealing member (a) having a concave portion such that said concave portion is extended to  
either side of said sealing member (a) from a central position of said sealing member (a) so  
as to have a peripheral portion which surrounds said concave portion, and said two sealing  
members (a) and (b) being arranged to oppose to each other such that the face of said  
concave portion of said sealing member (a) is faced to said sealing member (b) through  
said single battery main body, characterized in that said sealing member (a) has a  
peripheral collar portion (a-i) at said peripheral portion of said concave portion and said  
sealing member (b) has a peripheral collar portion (b-i) at a region thereof corresponding to  
said peripheral portion of said sealing member (a) wherein said collar portion (a-i) and said  
collar portion (b-i) are mutually welded, and either said sealing member (a) or said sealing  
member (b) is provided with a power output terminal having ~~[[an]]~~ electrical continuity  
with said cathode of said single battery main body, a power output terminal having  
electrical continuity with said anode of said single battery main body and an insulating  
portion for insulating said power output terminals.

2. (Currently amended) A rechargeable lithium battery which comprises a battery main body comprising at least a cathode, an anode, and an ion conductor enclosed between a pair of a sealing member (a) and a sealing member (b), each of said sealing member (a) and said sealing member (b) having a concave portion such that said concave portion is extended to either side of said sealing member from a central position of said sealing member so as to have a peripheral portion which surrounds said concave portion, and said two sealing members (a) and (b) being arranged to oppose to each other such that the face of said concave portion of said sealing member (a) and the face of said concave portion of said sealing member (b) are opposed to each other through said battery main body, characterized in that said sealing member (a) has a peripheral collar portion (a-i) at said peripheral portion of said concave portion and said sealing member (b) has a peripheral collar portion (b-i) at said peripheral portion of said concave portion so as to correspond to said peripheral collar portion (a-i) wherein said collar portion (a-i) and said collar portion (b-i) are mutually welded, and either said sealing member (a) or said sealing member (b) is provided with a power output terminal having electrical continuity with said cathode of said battery main body, a power output terminal having electrical continuity with said anode of said battery main body and an insulating portion for insulating said power output terminals according to claim 1,

wherein said sealing member (b) also has a concave portion such that said concave portion is extended to either side of said sealing member (b) from a central position of said sealing member (b) so as to have a peripheral portion which surrounds said concave portion and said peripheral portion comprises said collar portion (b-i).

3. (Previously Presented) A rechargeable lithium battery according to claim 1, wherein each of said sealing member (a) and said sealing member (b) principally comprises one or more metallic materials selected from the group consisting of a stainless steel material, a nickel material, a nickel-plated iron material, an aluminum material, and a copper material.

4. (Currently amended) A rechargeable lithium battery according to claim 1, wherein each of said collar portion (a-i) and said collar portion ~~(b-i)~~ have (b-i) has a width in a range of from 0.5 mm to 3.0 mm.

5. (Original) A rechargeable lithium battery according to claim 1, wherein said concave portion of said sealing member (a) is shaped to have a cross section in a substantially symmetrical trapezoidal form.

6. (Original) A rechargeable lithium battery according to claim 5, wherein said symmetrical trapezoidal form as said concave portion has an inclination in a range of from 5° to 45°.

7. (Currently amended) A rechargeable lithium battery according to claim 2, wherein said concave portion of each of said sealing member (a) and said sealing member (b) is shaped to have a cross section in a substantially symmetrical trapezoidal form.

8. (Original) A rechargeable lithium battery according to claim 7, wherein said symmetrical trapezoidal form as said concave portion has an inclination in a range of from 5° to 45°.

9. (Cancelled).

10. (Currently amended) A rechargeable lithium battery according to claim 1 [[9]], wherein said power output terminal having electrical continuity with said cathode and said power output terminal having electrical continuity with said anode ~~cathode power output terminal and said anode power output terminal~~ are situated at a position in said concave portion of said sealing member (a) which is 15 mm or less distant from a circumferential face of said concave portion.

11. (Original) A rechargeable lithium battery according to claim 1, wherein at least said sealing member (a) has a region constituted by a plastic material.

12. (Original) A rechargeable lithium battery according to claim 1, wherein said sealing member (a) or said sealing member (b) has an internal pressure release vent.

13. (Currently amended) A rechargeable lithium battery according to claim 12 [[1]], wherein said internal pressure release vent comprises a plug comprising a thin film, a rubber plug or a spring.

14. (Original) A rechargeable lithium battery according to claim 1, wherein an internal pressure release vent is provided in said insulating portion.

15. (Original) A rechargeable lithium battery according to claim 1, wherein said insulating portion comprises a plastic material.

b 16. (Original) A rechargeable lithium battery according to claim 1, wherein said insulating portion comprises a plastic material, an internal pressure release vent is provided in said insulating portion, and said internal pressure release vent comprises a plug comprising a thin film formed of said plastic material constituting said insulating portion.

17. (Currently Amended) A rechargeable lithium battery according to claim 1, wherein said power output terminals includes a cathode power output terminal electrically connected to said cathode of said single battery main body and an anode power output terminal electrically connected to said anode of said single battery main body, at least said cathode has a cathode lead portion, and said cathode power output terminal is joined with said cathode lead portion through a cathode power output lead comprising a clad material.

18. (Previously Presented) A rechargeable lithium battery according to claim 17, wherein said clad material comprises a material selected from the group consisting of a nickel material, a titanium material and a copper material, or a material containing an element constituting said cathode power output terminal as a main

constituent, and a material containing an element constituting said cathode lead portion as a main constituent.

19. (Currently Amended) A rechargeable lithium battery according to claim 1, wherein said anode of said single battery main body has an anode active material containing a material capable of being alloyed with lithium.

20 to 25 (Cancelled).

26. (New) A rechargeable lithium battery according to claim 2, wherein each of said sealing member (a) and said sealing member (b) principally comprises one or more metallic materials selected from the group consisting of a stainless steel material, a nickel material, a nickel-plated iron material, an aluminum material, and a copper material.

27. (New) A rechargeable lithium battery according to claim 2, wherein each of said collar portion (a-i) and said collar portion (b-i) has a width in a range of from 0.5 mm to 3.0 mm.

28. (New) A rechargeable lithium battery according to claim 2, wherein said power output terminal having electrical continuity with said cathode and said power output terminal having electrical continuity with said anode are situated at a position in said concave portion of said sealing member (a) which is 15 mm or less distant from a circumferential face of said concave portion.

29. (New) A rechargeable lithium battery according to claim 2, wherein at least said sealing member (a) has a region constituted by a plastic material.

30. (New) A rechargeable lithium battery according to claim 2, wherein said sealing member (a) or said sealing member (b) has an internal pressure release vent.

31. (New) A rechargeable lithium battery according to claim 30, wherein said internal pressure release vent comprises a plug comprising a thin film, a rubber plug or a spring.

32. (New) A rechargeable lithium battery according to claim 2, wherein an internal pressure release vent is provided in said insulating portion.

33. (New) A rechargeable lithium battery according to claim 2, wherein said insulating portion comprises a plastic material.

34. (New) A rechargeable lithium battery according to claim 2, wherein said insulating portion comprises a plastic material, an internal pressure release vent is provided in said insulating portion, and said internal pressure release vent comprises a plug comprising a thin film formed of said plastic material constituting said insulating portion.

35. (New) A rechargeable lithium battery according to claim 2, wherein said power output terminals include a cathode power output terminal electrically connected to said cathode of said battery main body and an anode power output terminal electrically connected to said anode of said battery main body, at least said cathode has a cathode lead

portion, and said cathode power output terminal is joined with said cathode lead portion through a cathode power output lead comprising a clad material.

36. (New) A rechargeable lithium battery according to claim 35, wherein said clad material comprises a material selected from the group consisting of a nickel material, a titanium material and a copper material, or a material containing an element constituting said cathode power output terminal as a main constituent, and a material containing an element constituting said cathode lead portion as a main constituent.

37. (New) A rechargeable lithium battery according to claim 2, wherein said anode of said battery main body has an anode active material containing a material capable of being alloyed with lithium.

---